

**Saugkupplungen mit Bund**  
**Suction Hose Couplings with security collar**



nach DIN 2817 – 3 **ohne Halbschalen**

according DIN 2817 – 3 **without clamps**



Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------

Storz Size	KA (mm) Lug	D (mm) Diameter	L (mm) Length	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
<b>25-D</b>	31	19	73	0,30	DN 20	13-031019-30	
		19	73	0,28	DN 20	13-031019-43	
		25	75	0,11	DN 25	13-031025-10	
		25	73	0,33	DN 25	13-031025-30	
		25	75	0,31	DN 25	13-031025-43	
<b>52-C</b>	66	32	95	1,16	DN 32	13-066032-43	
		38	90	0,40	DN 40	13-066038-10	
		38	95	1,14	DN 40	13-066038-43	
		50	95	0,41	DN 50	13-066050-10	
		50	95	0,77	Stahlstutzen tailpiece steel	13-066050-50	
		50	95	1,08	DN 50	13-066050-30	
<b>65</b>	81	50	95	1,03	DN 50	13-066050-43	
		50	95	1,50	DN 50	13-081050-43	
<b>75-B</b>	89	63	115	0,71	DN 65	13-089063-10	
		75	105	0,70	DN 80	13-089075-10	
		75	105	1,58	Stahlstutzen tailpiece steel	13-089075-50	
		75	105	2,27	DN 80	13-089075-43	
<b>100</b>	115	100	195	1,39	DN 100	13-115100-10	
<b>110-A</b>	133	100	145	1,67	DN 100	13-133100-10	
		100	145	4,49	DN 100	13-133100-43	
<b>125</b>	148	125	190	2,34	DN 125	13-148125-10	
<b>150</b>	160	150	250	3,61	DN 150	13-160150-10	

Geeignet für dickwandige Gummischläuche

Suitable for heavy-wall rubber hoses