

## Knaggen mit Außengewinde-Stutzen, drehbar Heads with male thread-tail, swivel




Dichtung: Nitril-Kautschuk schwarz / weiß  
Viton Dichtung bei V4A

Seal: Nitrile rubber black / white  
Fluoro rubber - Stainless steel

Gewinde - thread: **DIN ISO 228**

Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------



Storz Size	KA (mm) Lug	Außengewinde (w) Male thread	Weight (kg)	Ident-No.	Euro
<b>25-D</b>	31	G ¾ "	0,29	24-031075-30	
		G 1 "	0,35	24-031100-30	
<b>52-C</b>	66	G 1½ "	0,41	24-066150-10	
		G 2 "	0,39	24-066200-10	
		G 2 "	1,17	24-066200-30	
		G 2 "	1,10	24-066200-43	
<b>65</b>	81	G 1½ "	0,50	24-081150-10	
		G 2 "	0,53	24-081200-10	
		G 2½ "	0,55	24-081250-10	
		G 3 "	0,81	24-081300-10	
<b>75-B</b>	89	G 2 "	0,78	24-089200-10	
		G 2 "	2,25	24-089200-43	
		G 2½ "	0,55	24-089250-10	
		G 2½ "	1,48	24-089250-43	
		G 3 "	0,96	24-089300-10	
<b>90</b>	105	G 3 "	0,91	24-105300-10	
<b>100</b>	115	G 3 "	0,87	24-115300-10	
		G 4 "	1,59	24-115400-10	
<b>110-A</b>	133	G 3 "	1,54	24-133300-10	
		G 4 "	1,38	24-133400-10	
		G 4 "	3,86	24-133400-43	
<b>125</b>	148	G 4 "	1,80	24-148400-10	
		G 5 "	1,90	24-148500-10	
<b>150</b>	160	G 4½ "	2,61	24-160450-10	
		G 5 "	2,54	24-160500-10	
		G 6 "	3,84	24-160600-10	

Auf Wunsch: obige Teile mit Verriegelung (siehe Seite 7)

On demand: above parts with locking device (see page 7)