


**Festkupplungen mit Innengew. NPT, NH, NPSH, NSW**  
**Adapters with female thread NPT, NH, NPSH, NSW**



Dichtung: Nitril-Kautschuk schwarz / weiß  
 Viton Dichtung bei V4A

Seal: Nitrile rubber black / white  
 Fluoro rubber - Stainless steel



Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------

Storz Size	KA (mm) Lug	Innengewinde Female thread	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
<b>25-D</b>	31	1/2" NPT	0,08		21-031050-19	
		1/2" NPT	0,25		21-031050-39	
		3/4" NPT	0,08		21-031075-19	
		3/4" NPT	0,23		21-031075-39	
		1" NPT	0,09		21-031100-19	
		1" NPT	0,24		21-031100-39	
		1" NPT	0,21		21-031100-49	
		1" NH	0,08		21-031100-18	
		1" NPSH	0,09		21-031100-17	
<b>38</b>	51	1 1/4" NPT	0,17		21-051125-19	
		1 1/2" NPT	0,16		21-051150-19	
		2" NPT	0,18		21-051200-19	
		1 1/2" NH	0,14		21-051150-18	
		1 1/2" NPSH	0,15		21-051150-17	
<b>52-C</b>	66	1 1/2" NPT	0,28		21-066150-19	
		2" NPT	0,28		21-066200-19	
		2" NPT	0,81		21-066200-39	
		2 1/2" NPT	0,28		21-066250-19	
		1 1/2" NH	0,27		21-066150-18	
		1 1/2" NH	0,94		21-066150-38	
		2 1/2" NH	0,27		21-066250-18	
		1 1/2" NPSH	0,28		21-066150-17	
		2" NPSH	0,28		21-066200-17	
		2 1/2" NPSH	0,28		21-066250-17	
<b>65</b>	81	2 1/2" NPT	0,41		21-081250-19	
		2 1/2" NH	0,49		21-081250-18	
		2 1/2" NPSH	0,40		21-081250-17	
		5 1/5 NSW	0,47		21-081520-10	

Storz Size	KA (mm) Lug	Außengewinde Male thread	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
<b>75-B</b>	89	2 " NPT	0,43		21-089200-19	
		2½ " NPT	0,37		21-089250-19	
		3 " NPT	0,40		21-089300-19	
		2½ " NH	0,41		21-089250-18	
		2 " NPSH	0,43		21-089200-18	
		2½ " NPSH	0,43		21-089250-17	
		3 " NPSH	0,42		21-089300-17	
<b>100</b>	115	4 " NPT	0,81		21-115400-19	
		2½ " NH	1,20		21-115250-18	
		3 " NH	1,20		21-115300-18	
		4 " NH	0,80		21-115400-18	
		4½ " NH	1,90		21-115450-18	
		5 " NH	2,00		21-115500-18	
		6 " NH	2,10		21-115600-18	
		4 " NPSH	0,85		21-115400-17	
<b>110-A</b>	133	4 " NPT	1,06		21-133400-19	
		4 " NH	1,08		21-133400-18	
		4½ " NH	1,64		21-133450-18	
		4 " NPSH	1,09		21-133400-17	
		5 " NPT	1,38		21-148500-19	
		2½ " NH	2,10		21-148250-18	
		3 " NH	2,10		21-148300-18	
<b>125</b>	148	4 " NH	1,80		21-148400-18	
		4½ " NH	1,35		21-148450-18	
		5 " NH	2,40		21-148500-18	
		6 " NH	2,50		21-148600-18	
<b>150</b>	160	6 " NPT	1,79		21-160600-19	

Drehbare Ausführung auf Anfrage.  
 Swivel version on request.

**NPT** = Kegeliges Rohrgewinde 60°  
 Taper Pipe Thread acc. ANSI B 1.20.1-1983 (USA)

**NH** = Zylindrisches Gewinde 60°  
 NST National Standard Thread for fire hose connections acc. NFPA 1963 (USA)

**NPSH** = Zylindrisches Rohrgewinde 60°  
 Standard Straight Hose Coupling Thread acc. ANSI B 2.4-1966 (USA)